

河北省泊头市远东泵业制造有限公司（远东高温齿轮油泵厂）是一个集先进技术和现代化管理手段为一体的泵类研究开发制造企业。具有完善的生产体系。可为用户设计制造各种不同类型的专业泵。本厂以一流的生产水平，严格按ISO9002质量保证体系运行。优质的产品、售后服务以及良好的信用，使产品畅销不衰，赢得了用户的普遍赞誉。

RCB系列保温泵

适用范围

该泵适用于输送无腐蚀性、不含固体颗粒、温度不高于200°C的重油、沥青、胶类、树脂、洗涤剂、船用等各类在常温下有凝固性及高寒地区室外安装和工艺过程中要求保温的场合。

主要特征

该泵的泵体设有空心夹层，并设有进出口接口，可用于导热油、蒸气、热水、冷水等媒体对输送的液体和泵进行加热、保温及冷却。当输送介质的粘度大于1500cst时，应采用减速传动方式。一般情况下采用泵与电机直联的传动方式。

RCB全不锈钢系列保温泵

可输送化工、有色金属、冶金、造纸、军工科研、农药、洗涤剂等行业所需的介质，介质中不含固体颗粒。

经营宗旨

本厂将以高度的责任感，不断技术创新，愿承接客户提出的一切特殊型号的泵类设计和制造，竭诚为用户服务。

As a research, developing and manufacturing enterprise with the advanced technique and modern management means, Yuandong Pumps Manufacturing Co., Ltd. (Yuandong High-temp. Gear Oil Pump Factory) of Botou City, Hebei Province has established a complete production system and can design and manufacture various kinds of pump for the customer. The company has already reached the first-class production capability based on ISO9002 international quality system. The advanced products, excellent after-sale services and high-reputation have made the products in hot sale all the time and made the company highly appreciated by the customers.

RCB series Heat-preservation Gear Pumps

Applications:

The pumps are applicable for conveying heavy oil, asphaltum, thermal sol, glues, resin, scour, painting, etc. which are non-corrosive and free-of-particles when their temperature is lower than 200C. They are also applied to the situations when solidification of the conveyed medium occurs in the case of normal temperature, the heat-preservation shall be required in the production process and they are installed in the extremely cold regions.

Main features:

The pump and conveyed liquid shall be heated, heat-preserved that make use of heat-conducting oil, steam, thermal water and cooling water, etc. going through the motorcase's hollow interlayer. The speed reduction mode shall be adopted when the viscosity of the conveying medium is more than 1500CST. In general case, the pump can be directly connected with the motor by the means of a pair of coupeing.

RCB series Stainless Steel Heating-preservation Gear Pumps

The pump shall be adopted for conveying the medium without solid particles, such as chemical industrial products, nonferrous metal, metallurgical products, military scientific products, pesticide and scour, etc.

Operational Philosophy

Based on the high obligation and consecutive technical innovation, the company will willingly undertake all the design and manufacturing task for various pumps required by the customers and shall provide honest services.



RCB 型 齿 轮 保 温 泵 技 术 参 数 表

Technical Specifications for RCB Series Heat-preservation Gear Pumps

型号规格 Model	口 径 Port Size: (mm)	流 量 Flow Volume		排出压力 Exhausting Pressure Mpa	吸入真空高度 Extrusion Vacuum M	工作温度 Working temperature (°C)	电 动 机 Motor	
		L/min	m ³ /h				功率 (KW) Power	型 号 Type
RCB- 1/0.36 1/0.8	φ16	16.6	1	0.36 0.8	5	180	1.1 1.5	Y90S-4 Y90L-4
RCB- 2/0.36 2/0.8	φ25	33.3	2	0.36 0.8	5	180	1.5 2.2	Y90L-4 Y100L1-4
RCB- 3/0.36 3/0.8	φ25	50	3	0.36 0.8	5	180	1.5 2.2	Y100L-6 Y112M-6
RCB- 5/0.36 5/0.8	φ40	83.3	5	0.36 0.8	5	180	2.2 3	Y100L-4 Y132S-6
RCB- 6/0.36 6/0.8	φ40	100	5	0.36 0.8	5	180	2.2 4	Y100L1-4 Y112M-4
RCB- 8/0.36 8/0.8	φ50	133	8	0.36 0.8	5	180	3 4	Y132M1-6 Y132S-6
RCB- 10/0.36 10/0.8	φ50	166	12	0.36 0.8	5	180	4 5.5	Y112M-4 Y132S-4
RCB- 12/0.36 12/0.8	φ50	200	12	0.36 0.8	5	180	4 5.5	Y132M1-6 Y132M2-6
RCB- 18/0.36 18/0.8	φ70	300	18	0.36 0.8	5	180	5.5 7.5	Y132M2-6 Y160M-6
RCB- 29/0.36 29/0.8	φ70	483.3	29	0.36 0.8	5	180	5.5 7.5	Y132S-4 Y132M-4
RCB- 32/0.36 32/0.8	φ100	534	32	0.36 0.8	5	180	11 15	Y160L-6 Y180L-6
RCB- 38/0.28 38/0.8	φ100	633	38	0.28 0.8	5	180	11 15	Y160L-6 Y180L-6
RCB- 58/0.28 58/0.8	φ100	960	58	0.28 0.8	5	180	18.5 22	Y180M-4 Y180L-4
RCB- 72/0.8	φ150	1200	72	0.28	5	180	37	Y280S-8
RCB- 96/0.28	φ150	1600	96	0.28	5	180	45	Y280S-6
RCB- 110/0.28	φ200	1800	110	0.28	5	180	55	Y315S-8
RCB- 150/0.28	φ200	2500	150	0.28	5	180	75	Y315S-6
RCB- 170/0.28	φ250	2850	170	0.28	5	180	90	Y315L1-8
RCB- 230/0.28	φ250	3800	230	0.28	5	180	110	Y315L1-6

