

**SB****ALL STAINLESS STEEL PUMP****SB 370****SB 550****SB 750****Property:**

- a. AISI304 motor shell, impeller, diffuser, strainer, and nuts. Shaft in 316L special material.
- b. Italian double face mechanical seal, AC over-heat protector inside.
- c. Integrated plug, good water proof.
- d. Good appearance, small and light, easy to use and maintain.

**Usage:**

Especially for work places which have a high requirement for water quality, eg. Fountain, aquarium fish cultivation and industrial waste water, especially for draining industrial acid or alkaline waste water.

REMARKS: ITEMS WITH "F" ARE EQUIPPED WITH FLOAT SWITCH.

MODEL	POWER		VOLTAGE V	MAX FLOW m <sup>3</sup> /H	MAX HEAD m	OUTLET mm
	KW	HP				
<b>SB 0.37</b>	0.37	0.5	220	18	11	50
<b>SB 0.55</b>	0.55	0.75	220	18	12	50
<b>SB 0.75</b>	0.75	1	220	36	13	50
<b>SB 1.1</b>	1.1	1.5	220	40	15	50
<b>SB 1.5</b>	1.5	2	220	45	15	75
<b>SB 2.2</b>	2.2	3	220	58	15	85
<b>SB 3.7</b>	3.7	5	380	48	25	100
<b>SB 5.5</b>	5.5	7.5	380	72	28	100
<b>SB 7.5</b>	7.5	10	380	96	36	152

# ROTOR

## Sewage Submersible Pump

### SB

### ALL STAINLESS STEEL PUMP



SB 100



SB 1500



SB 2200-7500

