

JET



JET100P



JET-L1

Application Limits

- Suction head up to 9m
- Liquid temperature up to +40°C
- Ambient temperature up to +40°C
- Max. Working pressure: 7bar
- Voltage fluctuation should not exceed 10% of rated value.
- pH: 6.5 to 8.5

Advantages & Features

- The JET type self-priming pump
- High suction, with short time
- Different impeller material configuration

Performance Data

Model		Power		Max. Flow (m ³ /h)	Max. Head (m)	Head Range (m)	Max. Suction (m)	Packing Dim. L×W×H(mm)	G.W (kg)		20'Loading Qty. (pcs)	Inlet	Outlet
Single-Phase	Three-Phase	kW	HP						Single-Phase	Three-Phase			
JET100P	-	0.75	1	4.2	46	6~46	9	475×205×240	16.5	-	1480	G1	G1
JET550L1	-	0.55	0.75	3.6	41	7~41	9	480×205×225	14	-	1420	G1	G1
JET750L1	-	0.75	1	4.5	41	7~41	9	480×205×225	15.5	-	1420	G1	G1
JET1100L1	-	1.1	1.5	5.4	48	6~48	9	480×205×225	16.5	-	1420	G1	G1
JET1500L1	JETS1500L1	1.5	2	5.4	55	4.5~55	9	585×245×290	24.5	23.5	918	G1½	G1½
JET1800L1	JETS1800L1	1.8	2.5	6	62	3.5~62	9	585×245×290	25.5	24.5	918	G1½	G1½

Note: Single phase cable length is 0.3m, Europe plug; Three-phase cable length is 0.3m, no plug.