

PW



### Application Limits

- ⊙ Suction lift up to 8 m
- ⊙ Max. working pressure 5 bar
- ⊙ Liquid temperature up to +90°C
- ⊙ Ambient temperature up to +40°C
- ⊙ Voltage fluctuations should not exceed 10% of rate value

### Advantages & Features

- ⊙ Compact design, easy installation
- ⊙ A simple Pressure switch control automatically
- ⊙ Pump body insert of stainless sheet 304
- ⊙ Shaft extension is stainless steel 304
- ⊙ The impeller of copper alloy
- ⊙ High quality mechanical seal

### Performance Data

Model	Power		Max. Flow (m <sup>3</sup> /h)	Max. Head (m)	Head Range (m)	Max. Suction (m)	Packing Dim. L×W×H(mm)	G.W (kg)	20'Loading Qty. (pcs)	Inlet	Outlet
	kW	HP									
PW125	0.125	0.17	2.0	24	0 ~ 24	8	295×230×300	8.3	1600	G1	G1
PW250	0.25	0.34	2.2	30	0 ~ 30	8	295×230×300	9.0	1600	G1	G1
PW370	0.37	0.5	2.4	36	0 ~ 36	8	295×230×300	9.3	1600	G1	G1
PW550	0.55	0.75	3.0	42	0 ~ 42	8	315×245×325	12.1	1320	G1	G1
PW750	0.75	1	3.4	50	0 ~ 50	8	315×245×325	13.8	1320	G1	G1
PW1100	1.1	1.5	6.0	55	0 ~ 55	8	365×280×380	21.7	720	G1½	G1½
PW1100L	1.1	1.5	6.0	55	0 ~ 55	8	515×320×640	26.3	260	G1½	G1½

Note: The cable length of single phase pump is 1.3m, Europe plug.