





Position	Qty.	Description
		Rated voltage: 3 x 380-415 D/660-690 Y V Rated current: 21,2-19,6/12,2-11,6 A Starting current: 660-780 % Cos phi - power factor: 0,90-0,88 Rated speed: 2930-2940 rpm Efficiency: IE2 89,4% Motor efficiency at full load: 89.4 % Motor efficiency at 3/4 load: 92.5 % Motor efficiency at 1/2 load: 93.0 % Number of poles: 2 Enclosure class (IEC 34-5): 55 Dust/Jetting Insulation class (IEC 85): F Others: Net weight: 129 kg Gross weight: 149 kg

96580751 MTB 65-200/183 50 Hz



Description	Value
General information:	
Product name:	MTB 65-200/183 A-F-A-BQQV
Product No:	96580751
EAN number:	5700831382003
Technical:	
Rated flow:	60 m³/h
Rated head:	32 m
Actual impeller diameter:	183 mm
Primary shaft seal:	BQQV
Curve tolerance:	ISO 9906:1999 Annex A
Pump version:	A
Materials:	
Pump housing:	Cast iron
	EN-JL1040
	ASTM A48-40 B
Impeller:	Cast iron
	EN-JL1030
	ASTM A48-30 B
Material code:	A
Installation:	
Maximum ambient temperature:	60 °C
Maximum operating pressure:	16 bar
Flange standard:	DIN
Connect code:	F
Pump inlet:	DN 80
Pump outlet:	DN 65
Pressure rating:	PN 16
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 90 °C
Liquid temperature during operation:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Motor type:	160MB
IE Efficiency class:	IE2
Rated power - P2:	11 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-415 D/660-690 Y V
Rated current:	21,2-19,6/12,2-11,6 A
Starting current:	660-780 %
Cos phi - power factor:	0,90-0,88
Rated speed:	2930-2940 rpm
Efficiency:	IE2 89,4%
Motor efficiency at full load:	89.4 %
Motor efficiency at 3/4 load:	92.5 %
Motor efficiency at 1/2 load:	93.0 %
Number of poles:	2
Enclosure class (IEC 34-5):	55 Dust/Jetting
Insulation class (IEC 85):	F
Motor protec:	PTC
Motor No:	87410028
Motor range:	Standard
Others:	
Net weight:	129 kg
Gross weight:	149 kg



96580751 MTB 65-200/183 50 Hz

